


#### **Outline Dimension:**





#### **Oil-Water Separator UF-10K**























## **UNIKAS INDUSTRIAL INC.**

- : 455 Nishibara, Nagi-cho, Katsuta-gun, Okayama, 708-1306 Japan HQ & Factory TEL:+81 (0)868 36 3131 FAX:+81 (0)868 36 6209
- Osaka Operation : 7F Nikken Bldg, 2-1-9 Itachibori, Nishi-ku,Osaka, 550-0012 Japan TEL:+81 6 6535 4871 FAX:+81 6 6535 4874 E-Mail : eigyou@unikas.co.jp

#### http://www.unikas.co.jp

\* Before products operation, read the attached instruction manuals thoroughly the respective supplied instruction manual. \* The contents of this catalog are subject to change without prior notice.



MHS-30VXII MHS-32VX MHS-32VH MHS-36VX MHS-28G·B MHS-32G·B MHS-32UB MHS-40Bi MHS-L40Bi

# MHS series

#### Feather:

MHS Series of Manual Hydraulic Steering System are suitable for both Pleasure Boat and Small Fishing Boat, designed to add safety, reliability and comfort for cruising.

#### **HELM PUMP**



Designed light and compact with the minimum dash panel, and which provides the space can be effectively used in Cabin There are various displacement and which can be

combined with steering cylinders make it possible to correspond to the required specification of various kinds of boats.

#### **Option:** Fulfilling optional parts present your active cruising performance.



easy to remove air

# パネルフランジ FP138 HELM PUMP HM50B







STEERING WHEEL





#### **Application Guide:**



## MHS-VX Series



#### **Cylinder Selection Guide:**



# MHS-G/B/UB Series



Which are designed for Outboard-Front-Mount-Typed Steering.

System Model	Max. Torque (N-m)	Wheel Turn lock to lock (rev)	Helm Pump Displacement (cc)	Cylinder	Tubing
MHS-32VXS	659	4.5	HM50 26	32VXS	3/8 HP Hose
MHS-32VX	659	6.9	HM50 20	32VX	3/8 HP Hose
MHS-32VH	659	6.9	HM50 20	32VH	3/8 HP Hose
MHS-36VX	1043	7.3	HM50	36VX	3/8 HP Hose

#### Specification of MHS-VX Series:

- \* Above Applications are different in each type of hull only as a



Component kits come complete with Helm Pump, Steering Cylinder, HP-Hose/Fittings, Hydraulic Oil/Filler Kit and Manual needed for an install in One Packing Case, as showing the picture of Component Kit : MHS-32B

Speeds up air-removal by utilizing Stop Valve equipped with Helm Pump.Tubing HP hoses are simple to work as to cut length and compress to fittings. The fittings at cylinder are made of stainless steel to add the corrosion resistant.

#### Specification of MHS-G/B/UB Series:

System Model	Max. Torque (N-m)	Wheel Turn lock to lock (rev)	Helm Pump Displacement (cc)	Cylinder	Tubing
MHS-28G	468	4.9	HM50 20	28G	3/8 HP Hose
MHS-28B	468	4.9	HM50 20	28B	3/8 HP Hose
MHS-32G	668	7.0	HM50 20	32G	3/8 HP Hose
MHS-32B	668	7.0	HM50 20	32B	3/8 HP Hose
MHS-32UB	944	7.7/6.6	HM50 23	32UB	3/8 HP Hose
MHS-40Bi	869	7.8	HM50 23	40Bi	3/8 HP Hose
MHS-L40Bi	1068	9.6	HM50 23	L40Bi	3/8 HP Hose